## mar plast group

TRACTOR T4000

ELECTRICPORTER





## General features and advantages

FANTOZZI T4000 tractor is suitable to tow up to 4000 Kg. inside and outside the factory. The T4000 electric tractor assures the maximum driving comfort together with safe driving and production increase.

#### Intensive use

The high numbers of scheduled working handlings and meanwhile the unexpected emergencies and precision, need reliable tools always versatile and available to carryout continuous work granting high quality levels.

Slim and strong FANTOZZI T4000 is suitable to drive into small and complex ways; working proof resistant inside the stocking area and factory on flat floors.

### Increase on productivity

FANTOZZI T4000 tractor answers the modern concept of logistic, goods handling and people's transport which require more and more skilled and dedicated working instruments suitable to reach the best compromise between working time, working quality & precision, and operator's safety & satisfaction.

During handling of unpacked goods or single pieces - without pallets or loading units - FANTOZZI T4000 produces a significant increase in productivity, it means much more work arranged shortly and saving of human resources.

### Driving comfort

FANTOZZI T4000 has comfortable driving position, easy access to the operating control unit, limited height of the platform and comfortable adjustable seat: these allow the operator to drive longtime on safety and correct position, in accordance with ergonomic standards.

Accessories such as goods-holder or objects support make the daily operations easier; whereas the front and rear lights, side lights and covering cab make the vehicle safer.



Maximum safety for operator, goods and environment The modern concept of safety is not only limited to the operator but to the complete "system": operator, goods, environment.

FANTOZZI T4000 is studied in accordance with current regulations as for accident-prevention, limited vibrations, industrial health, common protection etc, but mainly thinking on ethic responsibility and reliability as for working satisfaction and appreciation of human resources.

## Technical / manufacturing features

Motor

Equipped with 3000W motor - Loading capacity 900 Kg. - Towing capacity 4000 Kg.






Differential gear
Differential gear complete with shafts.
Shafts have supports connected to the aluminium body in order to make the structure safer.

### Chassis

Strong structure made of Fe37 with black embossing non-scratch epoxy painting. The structure reinforcements guarantee the maximum vehicle's reliability.





Electronic control unit
The electronic control unit allows the
speed-braking-acceleration
adjustments: these parameters
customize the use of FANTOZZI T4000.

### Battery

The vehicle is equipped with one traction battery 24V 480Ah (8 hours endurance).





Pedal accelerator
FANTOZZI T4000 is equipped with two acceleration pedals: one for the forward driving and the other for the backward driving. The pedals are placed under the steering wheel and can be operated by the right foot.

## Service brake Service brake pedal is operated by the left foot. The motor has a gradual counterbrake and finally the service brake enters automatically.





Adjustable steering wheel
The lever placed on the left side of the
steering wheel allows the adjustment in
accordance with operator's comfort.

### Emergency button

The red button placed near the driver's seat allows the instant stop and limits the risk of accident inside and outside the factory.





Steering wheel Simple, easy, essential, the steering wheel has:

- Control knob
- Lights switch
- Charge indicator display
- Warning buzzer
- Side lights lever
- Adjustable steering-wheel lever
- Starting key

### Towing hook

The FANTOZZI T4000 is equipped with adjustable towing hook: it helps the operator during every kind of towing operations.





Side lights

Side lights are not only in the rear position of the vehicle but also in left/right sides: this makes the vehicle safer during driving operations inside and outside the factory.



### Optionals

Rain-proof cab Iron made structure with black embossing painting, the cab is complete with left & right mirrors and PVC covering.

Roll bar Tubular iron structure with black embossing painting.







## Technical features VDI 2198

	1.1	Manufacturer		Fantozzi
Features	1.2	Model		T4000
	1.3	Traction		Electric
	1,4	Type of driving		Seated on board
ĮĒ.	1.5	Loading capacity	Q (t)	40
	1.9	Wheel axis	y (mm)	970
hts	2.1	Weight including batteries	Kg	890
Weights				
	3.1	Tyres (superelastic, pneumatic )		SE
aLLe	3.2	Front wheel dimensions		5.00 - 8
ructi	3.3	Rear wheel dimensions		5.00 - 8
Wheels / structure	3.5	Front wheel number (x = traction)		2
eels	3.5.1	Rear wheel number (x = traction)		2
₩	3.6	Front wheel track	b <sub>10</sub> (mm)	780
	3.7	Rear wheel track	b <sub>11</sub> (mm)	850
	4.7	Operator's protection height (cab)	h <sub>6</sub> (mm)	1060
	4.8	Operator's seat height	h <sub>7</sub> (mm)	860
	4.12	Towing hook height	h <sub>10</sub> (mm)	250
	4.13	Platform height (without loading)	h <sub>11</sub> (mm)	360
Suc	****	Clearance	h <sub>11</sub> (mm)	270
Basic dimensions	4.16	Loading platform length	l₃ (mm)	330
dime	4.17	Loading platform width	b <sub>9</sub> (mm)	950
sic	4.19	Total length	I <sub>1</sub> (mm)	2130
Ba	4.21	Total width	b <sub>1</sub> (mm)	950
		Working aisle width	(mm)	1150
		Intersecting aisle width	(mm)	1900
		Minimum rack width between 2 working aisles	(mm)	800
		90° Turning radius	(Wa mm)	1530
	5.1	Driving speed with full loading	km/h	8
es es	5.1.1	Driving speed without loading	km/h	10
Performances	5.8	Max. grade with full loading	%	5
form	5.10	Service brake		Electromechanical + hydraulic
Per	5.11	Parking brake		Electromechanical
*		Emergency brake		Electromechanical
_		Driver detection sensor		Mechanical
tor	6.1	Traction motor - capacity KB 60 min	kW	3
Electric motor	6.3	Battery		24V 480Ah
stric	6.4	Battery tension	UV	24V
Ele	6.4.1	Battery capacity	K 5 Ah	480Ah
	6.5	Battery weight	Kg	390
ers	8.1	Kind of transmission	Diff.	1:15,5
	8.4	Average noise for the operator	dB (A)	< 70
Others	8.5	Towing hook		Mechanical
	8.6	Steering gear		Wheel /
		Vibration to the operator		I

<sup>\*</sup> the performances refer to the vehicle in perfect conditions, with charged battery and regular motor maintenance





# Safe working. You can! You must!

### **ELECTRICPORTER RANGE 2007**







**PLATFORMS** 



**SCOOTERS** 



**HOSPITAL** 













moving safe. at work

Fantozzi Electric Carts S.r.l. Via Rosa Luxemburg, 24 42010 Rio Saliceto (RE) - Italy Tel. +39 0522 647192 Fax +39 0522 699479 info@fantozzi.com sales@fantozzi.com www.fantozzi.com