


PFEIFER-RENFROE clamp model MPC 1



with pivoting lifting shackle





For vertical lifting and 180° turning of, and lateral attachment to sheets, steel plates, girders and structural steel elements.

The "lock closed" feature guarantees the clamp to firmly grip the load even under unintentional release.

The MPC series replaces the following clamp models: CS and CA 2 with extended operating features.

Also available for super-hard loads up to 450 HB and with stainless steel gripping elements (see Page 77).



SWL kg	Gripping range A mm	Dimensions in mm							Weight approx. kg	Reference no.
		B	D	E	F	G	H	J		
1000	0-25	65	290	60	125	65	45	12	4.9	166788
1000	25-50	65	290	60	150	65	45	12	4.2	166790
2000	0-30	80	370	70	165	72	55	15	7.5	167546
2000	30-60	80	370	70	195	72	55	15	8.0	167552
3000	5-35	105	490	90	195	86	65	20	12.0	161490
3000	35-70	105	490	90	230	86	65	20	12.5	161491
5000	5-50	115	515	90	240	95	85	20	18.0	163216
5000	50-100	115	515	90	290	95	85	20	19.0	168275

PFEIFER-RENFROE clamp model MPC 2



with pivoting lifting shackle




For vertical lifting and 180° turning of, and lateral attachment to sheets, steel plates, girders and structural steel elements.

With "lock closed" and "lock open" feature enabling the clamp to firmly grip the load even under unintentional release. In "lock open" position the clamp can be advanced to the load, attached and locked.


Once the load has been set down and secured, the clamp – locked in the open position – can be lifted off by the crane.

The MPC series replaces the following clamp models: CS and CA 2 with extended operating features.

Also available for super-hard loads up to 450 HB and with stainless steel gripping elements (see Page 77).



SWL kg	Gripping range A mm	Dimensions in mm							Weight approx. kg	Reference no.
		B	D	E	F	G	H	J		
1000	0-25	65	290	60	125	65	45	12	5.0	166800
1000	25-50	65	290	60	150	65	45	12	4.8	166802
2000	0-30	80	370	70	165	72	55	15	8.4	167572
2000	30-60	80	370	70	195	72	55	15	8.0	167575
3000	5-35	105	490	90	195	86	65	20	12.0	161512
3000	35-70	105	490	90	230	86	65	20	13.9	161510
5000	5-50	115	515	90	240	95	85	20	22.6	168288
5000	50-100	115	515	90	290	95	85	20	19.0	168289



For main use of the MPC model series please see the attached drawing and the chart on page 87.