

CE the CargoMaster A-system and C-system correspond to the Guidelines 2006/42/EG of the European Community.

The company AAT Alber Antriebstechnik GmbH is licensed for DIN EN ISO 9001.2008

Technical data	A142	A350	C141	C141 Vario	CC160	CC200	C400	Vario-max
Lifting capacity	140 kg	350 kg	140 kg	140 kg	160 kg	200 kg	400 kg	170 kg / 160 kg *
ComfortStep	-	-	-	-	•	•	-	-
Battery display	-	-	-	-	•	•	-	-
Climbing speed / steps per minute (continually adjustable)	8 — 25	4 — 10	8 — 30	8 — 30	9 — 26	4 — 19	3 — 8	8 — 23
Range with one charge of the battery (Floors, depending on load)	30 — 50 Corresponds to: 80 kg approx. 1110 Steps 140 kg approx. 720 Steps	15 — 30 Corresponds to: 200 kg approx. 650 Steps 250 kg approx. 540 Steps 350 kg approx. 330 Steps	15 — 30	15 — 30	15 — 30	15 — 30	8 — 15	10 — 25
Height	1100 - 1700 mm	1195 - 1785 mm	1380 mm	1060 — 1400 mm	1065 — 1490 mm	1065 — 1490 mm	1512 mm	1060 — 1400 mm
Width	580 mm	590 mm	450 mm		466 mm	466 mm	564 mm	450 mm
Depth	470 mm	520 mm	300 mm		290 mm		782 mm	550 mm
Batteries	2 x 12 V / 7,2 Ah		2 x 12 V / 5 Ah					
DC motor	24 V							
Weight, battery pack	6 kg		4,1 kg					
Total weight (including battery pack)	32 kg	49 kg	25,5 kg	26,7 kg	28,5 kg	29,9 kg	84,3 kg	35 kg

*Maximum lifting capacity (passenger transportation)