

## Cargo



Single sided step-stool in welded aluminium. Cargo is made of a resistant one-piece structure suitable to be used on machineries and for the access to loading platforms. The wide rungs are non-skid knurled plate and welded to a strong tubular structure (25x25 mm). Thanks to its wide base (50 cm), Cargo is very stable and user friendly. Rust can not corrode this material which is long lasting.



n.	m	m	cm	Kg	cm
1	0,24	2,24	52	2	30
2	0,48	2,48	58,5	4	54
3	0,72	2,72	62	6	78
4	0,96	2,96	64	8	104



VIDEO

- Non-skid rung dimensions: 45x20 cm
- Distance between steps: 24 cm
- Step depth: 20 cm
- Non-skid P.V.C. feet



Cargo with 2 steps and deeper platform



Side handrails




1 step Cargo stools



Cargo 3 steps with handel and wheels Kit



Optional special grid aluminium steps (supergrip for oil and snow)



Standard steps

### On request:

- Special sizes
- 2 Frontal wheels for trasport
- 2 Handles for lifting (including 2 wheels)
- Different dimension of the platform (max 80 cm)
- Permanent or detachable side handrail (left or right)
- Permanent or detachable front guardrail
- Distance between steps less than 24 cm
- Safety chain to protect the front landing



Cargo Special sizes

