

Castellana Maxi



According to EN131/7 is tested with 30 Kg overturning traction force at platform level

ON DEMAND SAFETY & PROTECTION AT 360°



Aluminium mobile warehouse stepladder with reinforced platform, guardrail and handrail. It is particularly suitable for heavy duty. Each step is firmly welded to the frame.

The front side is wide and easy to climb and it is strongly inclined (55°), so that climbing becomes easier thanks to both the non-skid reinforced steps (20-cm wide with a distance of 23 cm one from the other) and to the large handrail. The back of the ladder is perpendicular to the ground, allowing the user to approach a wall or a shelf front onwards.

The automatic braking system becomes operative when the ladder is open for use. When the ladder is moved with the raising arms, the rubber feet rise allowing the two wheels to move effortlessly over the ground.

- Base stabiliser with ergonomic feet and wheels Ø 125 mm
- Non-skid steps 20 cm
- Distance between steps 23 cm
- Frame profile 200x30 mm
- Guardrail height 100 cm
- Toeboard height 10 cm
- Large platform 53x92 cm
- Front width 60 cm
- Front part inclination 55°



Optional: Closable stabilizer (overall dimensions closed 100 cm)



VIDEO



Castellana Maxi 4WD (optional)

Note: Castellana Maxi will be produced and available with the foldable handles from June 2019 while stocks last of the previous model



n.	m	m	m	m	Kg
4	0,92	1,94	3,00	1,00x1,65	32,50
5	1,15	2,17	3,15	1,00x1,81	35,50
6	1,38	2,40	3,40	1,00x1,97	39,00
7	1,61	2,63	3,61	1,16x2,13	43,50
8*	1,84	2,85	3,85	1,16x2,29	46,00
9*	2,07	3,08	4,07	1,32x2,45	49,50
10**	2,30	3,31	4,30	1,32x2,62	53,00
11**	2,50	3,51	4,50	1,32x2,75	56,50
12**	2,76	3,77	4,80	1,48x2,94	60,00
14**	3,22	4,23	5,30	1,48x3,26	69,00

Note: The platform is considered as a step.
 In all models the stabilizer is disassembled for transport reasons.
 Higher models have stabilizer also on the front ramp (cm 101*/132**) Castellana 12 steps is according to EN131/7 just for indoor use.
 Castellana 14 steps is not according to EN131/7

On request:

- Short stabiliser (75 cm long) for use in narrow corridors (EN131 not possible)
- Short stabiliser with 2 wheels with brakes (95 cm long) for use in narrow corridors (EN131 not possible)
- Foldable stabiliser (from 100 cm get to 150 cm) for use in narrow corridors
- 4WD: kit of 4 pivoting wheels Ø 100 mm with brakes (EN131 not possible) (to be assembled by the producer)
- Non-closing fixed ladder
- Foldable ladder system by hinges
- Protection chain (to be assembled by the producer)
- Fiberglass version for chemical or food companies (to be assembled by the producer)

