




Day



DAY ladders above m 3 can be used in compliance with the European Standard only with purchase and assembly of the stabilizer



Optional stabilizer



EN131 TESTED BY TÜV



ISO 9000 UNI EN 287/1 EN ISO 9606/2

TECHNICAL FEATURES DAY

Steps n°	A cm	B cm	C cm	D cm	E cm	F cm	G cm	Weight Kg
5	216	89	127	62,5	60	26	239	11
6	242	89	153	73,0	60	26	267	12
7	268	89	179	83,5	60	26	295	13
8	294	89	205	94,0	60	26	323	14
9	320	89	231	104,5	60	26	351	15
10	346	89	257	115,0	60	26	379	16
11	372	89	283	125,5	60	26	407	17
12	398	89	309	136,0	60	26	435	18
13	424	89	335	146,5	60	26	463	19
14	450	89	361	157,0	60	26	491	20
15	476	89	387	167,5	60	26	519	21
16	502	89	413	178,0	60	26	547	22
17	528	89	439	188,5	60	26	575	23
18	554	89	465	199,0	60	26	603	24
19	580	89	491	209,5	60	26	631	25
20	606	89	517	220,0	60	26	659	26
21	632	89	543	230,5	60	26	687	27
22	658	89	569	241,0	60	26	715	28


On request:

- Optional standard adjustable feet 55 x 120 mm
- Optional large adjustable feet 59 x 178 mm
- Optional stabilizer: according to the European Standard EN131/1/2015 for models over 3 m. DAY models over m 3 are designed for assembling the stabilizer by the customer.



Welded professional single section aluminium ladder for access to attics and lofts.



DAY step width cm 10



DAY MAXI step width cm 20



DAY MAXI

TECHNICAL FEATURES DAY MAXI

Steps n°	A cm	B cm	C cm	D cm	E cm	F cm	G cm	Weight Kg
5	217	102	115	102,0	60	43	278	19
6	240	102	138	118,0	60	43	306	21
7	263	102	161	134,0	60	43	334	24
8	285	102	184	150,0	60	43	362	26
9	308	102	207	166,0	60	43	390	28
10	331	102	230	182,5	60	43	418	31
11	354	102	253	198,5	60	43	446	33
12	377	102	276	215,0	60	43	476	36
13	400	102	299	227,0	60	43	502	38
14	423	102	322	247,0	60	43	530	41

- Comfortable and light
- Handrail on both sides
- Non-skid rubber feet
- Upper PVC feet
- Distance between steps: 265 mm DAY - 230 mm DAY MAXI
- Non-skid steps 10 cm DAY - 20 cm DAY MAXI
- Guardrail height: cm 89 DAY - cm 100 DAY MAXI
- Ramps width cm 60

Stabilizers codes:

- SALLARG01 stabilizer 08/11 steps mm 1010
- SALLARG02 stabilizer 12/16 steps mm 1160
- SALLARG03 stabilizer 17/22 steps mm 1330



Reinforcements on all step available (additional price)