


Specifications



| MODELS | GL™-4 | | GL™-8 | | GL™-10 | | GL™-12 | |
|---|---------------|--------|---------------|--------|--------------|--------|--------------|--------|
| MEASUREMENTS | US | Metric | US | Metric | US | Metric | US | Metric |
| A Height - stowed ^{1,2,3} | 5 ft 7.5 in | 1.72 m | 5 ft 7.5 in | 1.72 m | 6 ft 6.5 in | 2.00 m | 6 ft 6.5 in | 2.00 m |
| maximum forks down | 4 ft 1.5 in | 1.26 m | 8 ft 3 in | 2.51 m | 9 ft 10.5 in | 3.01 m | 12 ft | 3.66 m |
| maximum forks up | 5 ft 11 in | 1.80 m | 10 ft .5 in | 3.06 m | 11 ft 8 in | 3.56 m | 13 ft 9.5 in | 4.20 m |
| minimum forks down | 3.5 in | .09 m | 3.5 in | .09 m | 2 in | .05 m | 2 in | .05 m |
| STANDARD BASE | | | | | | | | |
| B Length - stowed | 1 ft | .30 m | 1 ft | .30 m | — | — | — | — |
| operating | 2 ft 10.75 in | .88 m | 2 ft 10.75 in | .88 m | — | — | — | — |
| C Width - outside | 2 ft .75 in | .63 m | 2 ft .75 in | .63 m | — | — | — | — |
| Weight - standard caster options | 113 lbs | 51 kg | 132 lbs | 60 kg | — | — | — | — |
| pneumatic caster options | 117 lbs | 53 kg | 136 lbs | 62 kg | — | — | — | — |
| STRADDLE BASE | | | | | | | | |
| Length - stowed | 1 ft 7.25 in | .49 m | 1 ft 7.25 in | .49 m | 1 ft 7.25 in | .49 m | 1 ft 7.25 in | .49 m |
| operating | 3 ft 7 in | 1.09 m | 3 ft 7 in | 1.09 m | 3 ft 7 in | 1.09 m | 3 ft 7 in | 1.09 m |
| Width - stowed ⁴ | 2 ft 4.75 in | .73 m | 2 ft 4.75 in | .73 m | 2 ft 4.75 in | .73 m | 2 ft 4.75 in | .73 m |
| maximum ⁴ | 3 ft 7.5 in | 1.10 m | 3 ft 7.5 in | 1.10 m | 3 ft 7.5 in | 1.10 m | 3 ft 7.5 in | 1.10 m |
| maximum inside | 3 ft | .91 m | 3 ft | .91 m | 3 ft | .91 m | 3 ft | .91 m |
| Weight - standard caster options | 126 lbs | 57 kg | 145 lbs | 66 kg | 149 lbs | 68 kg | 154 lbs | 70 kg |
| pneumatic caster options | 130 lbs | 59 kg | 149 lbs | 68 kg | 153 lbs | 69 kg | 158 lbs | 72 kg |
| 4-point caster option | 139 lbs | 63 kg | 158 lbs | 72 kg | 162 lbs | 73 kg | 167 lbs | 76 kg |
| COUNTERWEIGHT BASE | | | | | | | | |
| Length - operating | 2 ft 4.5 in | .72 m | 2 ft 4.5 in | .72 m | 2 ft 4.5 in | .72 m | — | — |
| Width - stowed ⁴ | 2 ft 4.75 in | .73 m | 2 ft 4.75 in | .73 m | 2 ft 4.75 in | .73 m | — | — |
| maximum ⁴ | 3 ft 7.5 in | 1.10 m | 3 ft 7.5 in | 1.10 m | 3 ft 7.5 in | 1.10 m | — | — |
| maximum inside | 3 ft | .91 m | 3 ft | .91 m | 3 ft | .91 m | — | — |
| Weight - standard caster options | 392 lbs | 178 kg | 411 lbs | 186 kg | 433 lbs | 196 kg | — | — |

| PRODUCTIVITY | | | | | | | | |
|--|--------------|-----------|--------------|-----------|--------------|-----------|--------------|-----------|
| Load height minimum | 3.5 in | .09 m | 3.5 in | .09 m | 3.5 in | .09 m | 3.5 in | .09 m |
| Ground clearance - center ^{1,2,3} | .75 in | .02 m | .75 in | .02 m | .75 in | .02 m | .75 in | .02 m |
| Average cranks - standard winch | 11.5/ft | 38/m | 11.5/ft | 38/m | 11.5/ft | 38/m | 11.5/ft | 38/m |
| electric winch | 2 in/sec | .05 m/sec | 2 in/sec | .05 m/sec | 2 in/sec | .05 m/sec | 2 in/sec | .05 m/sec |
| Fork length | 1 ft 10.5 in | .57 m | 1 ft 10.5 in | .57 m | 1 ft 10.5 in | .57 m | 1 ft 10.5 in | .57 m |
| Fork width | 1 ft 8.5 in | .52 m | 1 ft 8.5 in | .52 m | 1 ft 8.5 in | .52 m | 1 ft 8.5 in | .52 m |
| Load platform length | 1 ft 11 in | .58 m | 1 ft 11 in | .58 m | 1 ft 11 in | .58 m | 1 ft 11 in | .58 m |
| Load platform width | 1 ft 10 in | .56 m | 1 ft 10 in | .56 m | 1 ft 10 in | .56 m | 1 ft 10 in | .56 m |
| Load capacity at 12 in (30 cm) load center | 500 lbs | 227 kg | 400 lbs | 181 kg | 350 lbs | 159 kg | 350 lbs | 159 kg |
| Boom length | 20.19 in | 51 cm | 20.19 in | 51 cm | 20.19 in | 51 cm | 20.19 in | 51 cm |
| Boom attachment points | 13.25/19 in | 34/48 cm | 13.25/19 in | 34/48 cm | 13.25/19 in | 34/48 cm | 13.25/19 in | 34/48 cm |

| POWER | |
|--------------|---|
| Power source | reversible standard winch or electric winch |

¹ The 10 in pneumatic rear wheel option will add 1 in (2.5 cm) to these specifications. ³ The 4-point caster option B will add 1 in (2.5 cm) to these specifications.
² The counterweight base will add 1 in (2.5 cm) to these specifications. ⁴ Outside dimensions.

Features

EASILY CONFIGURED TO MEET YOUR NEEDS

FORK OPTIONS

- Standard forks
- Load platform
- Boom

POWER OPTIONS

- Standard winch
- Electric winch

BASE OPTIONS

- Standard base (GL-4, -8 only)
- Straddle base (all units)
- Counterweight base (GL-4, -8, -10 only)

WHEEL/CASTER OPTIONS

Straddle and standard base

- 8 in (20 cm) non-marking rear wheels
- Pneumatic rear tire option
- 2 in (5 cm) dual wheel front swivel casters

Counterweight base

- 5 in (12 cm) rear swivel casters with side brakes
- 4 in (10 cm) fixed front wheels

Straddle base

- 4 point caster option

STANDARD FEATURES

MEASUREMENTS

GL™-4

- 5 ft 11 in (1.80 m) maximum lift height
- Up to 500 lb (227 kg) load capacity

GL™-8

- 10 ft .5 in (3.06 m) maximum lift height
- Up to 400 lb (181 kg) load capacity

GL™-10

- 11 ft 8 in (3.56 m) maximum lift height
- Up to 350 lb (159 kg) load capacity

GL™-12

- 13 ft 9.5 in (4.20 m) maximum lift height
- Up to 350 lb (159 kg) load capacity

PRODUCTIVITY

- Portable and compact design
- Lightweight durable aluminum construction
- Single door access
- Durable standard steel forks
- 8 in (20 cm) non-marking rear wheels and 2 in (5 cm) dual wheel front swivel casters (standard and straddle base only)
- 5 in (12 cm) rear swivel casters with side brakes and 4 in (10 cm) fixed front wheels (counterweight base only)
- Loads easily into a pickup truck for transporting
- Hold-down mechanism secures carriage during transport

POWER

- Standard winch
- Reversible winch handle for easy storage



OPTIONS & ACCESSORIES

PRODUCTIVITY

- Load platform
- Boom
- Aluminum ladder (standard and straddle base only)
- Pneumatic rear tires (standard and straddle base only)
- Foot-release brake (standard and straddle base only)
- Caster options

POWER

- Electric winch (straddle and counterweight base only)
- Winch operates while ladder is in use or stowed
- Caster option kit required for use with Straddle bases
- Electric winch option comes standard with battery and automatic charger that shuts off when fully charged.

Genie United States

18340 NE 76th Street
P.O. Box 97030
Redmond, Washington 98073-9730

Telephone **(425) 881-1800**
Toll Free in USA/Canada **800-536-1800**
Fax (425) 883-3475

Genie Europe

The Maltings
Wharf Road
Grantham NG31 6BH
U.K.

Telephone **+44 (0)1476 584333**
Fax +44 (0)1476 584334

Email: infoeurope@genieind.com

Distributed By:

Effective Date: July, 2007. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade-names of Terex Corporation, Genie Industries, Inc. and/or their subsidiaries in the U.S.A. and many other countries and all rights are reserved. Terex® is a Registered Trademark of Terex Corporation in the U.S.A. and many other countries. Genie® is a Registered Trademark of Genie Industries, Inc. in the U.S.A. and many other countries. Genie is a Terex Company. Copyright © 2007 Terex Corporation.