



Mobile platforms with flat steps equipped with comfortable platform, handrails and guardrails. Made of ribbed extruded aluminum. Supplied disassembled they can be easily assembled thanks to the detailed instruction booklet. The back frame of the PALCO LIGHT model is almost perpendicular to the ground in order to allow the operator to be very near to the machine/wall. The ladder always rests on the base feet and can be moved like a wheelbarrow by lifting it on the front wheels.

If the work platform exceeds one meter in height, it is advisable to equip the ladders with handrails on both sides.



Palco Light



n.	m	m	m	m	Kg
3	0,63	1,63	2,63	0,77x1,14	22,10
4	0,84	1,84	2,84	0,79x1,24	23,80
5	1,05	2,05	3,05	0,91x1,34	27,00
6	1,26	2,26	3,26	1,10x1,44	28,50
7	1,47	2,47	3,47	1,31x1,54	30,30
8	1,68	2,68	3,68	1,51x1,64	31,90

A handrail is included in the package - The platform is considered as a step

PALCO & PONTE LIGHT

- Rung depth: 8 cm
- Distance between steps: 23 cm
- Ramp C profile: 85x20mm
- Ramp inclination: 67°
- Toeboard height: 15 cm
- Ramp width: 60 cm
- Stabilizer starting from 5 steps
- Wooden platform cm 61x78
- Reinforced bars in galvanized steel
- Steps are fixed to the profiles by rivets (6 rivets every step)
- The ladder can be moved by 2 castors Ø 80 mm

On request:

- Additional handrail on the other side



Ponte Light



n.	m	m	m	m	cm	Kg
3	0,62	1,66	2,62	0,77x1,32	-	20,20
4	0,83	1,87	2,83	0,79x1,50	38	23,10
5	1,04	2,08	3,04	0,90x1,71	59	25,80
6	1,26	2,29	3,26	1,10x1,89	44	27,90
7	1,47	2,50	3,47	1,30x2,07	65	29,90
8	1,68	2,71	3,68	1,50x2,24	86	31,90

A double handrail is included in the package - The platform is considered as a step

On request:

- Additional double handrail on the other side



The compact packaging protects all components