

Professional aluminium stools produced according to the European standard EN14183. They are produced by welding the steps to the profiles, obtaining an ultra-resistant monolith. Equipped with reinforcements on the first step. They can be used up to the platform according to the European Standards.



VIDEO


Punto S



ISO 9000
UNI EN 287/1
EN ISO
9606/2



Professional double sided aluminium stepstool with large steps.



n.	m	m	cm	Kg	m
2	0,48	0,40	45,40	3,6	2,40
3	0,69	0,60	47,20	4,5	2,60
4	0,91	0,80	49,30	5,7	2,80
5	1,12	1,00	51,50	6,6	3,00

European standard UNIEN14183: with PUNTO S 2 and 3 steps the operator can stand on the last steps or on the platform even without a guardrail (optional). A 60 cm guardrail is mandatory only for the 4th and 5th steps.

- Ergonomic reinforced non-skid rubber feet
- Thermo-shrinkable plastic package with showcard
- Two devices block any accidental opening: anti opening/closing rigid bars and hinges in galvanized steel
- Non-skid aluminium steps 8 cm
- Distance between steps 20 cm
- Thickness when closed 22 cm
- Top platform 20x39 cm

- On demand (see numbers in the pictures):
- 1) Combination guardrail + 2 handrails of cm 60 (SPPLUS07/C)
Guardrail without handrails (SPPLUS07)
 - 2) Kit 2 wheels



Reinforcements on all step available (additional price)



VIDEO

Punto Large S



ISO 9000
UNI EN 287/1
EN ISO
9606/2



Professional double sided aluminium stepstool with flat steps. It is extremely wide for more working space.



n.	m	m	cm	Kg	m
2	0,48	0,40	75,30	4,9	2,40
3	0,69	0,60	77,30	6,7	2,60
4	0,91	0,80	79,30	8,5	2,80
5	1,12	1,00	83,00	10,3	3,00

European standard UNIEN14183: with PUNTO S 2 and 3 steps the operator can stand on the last steps or on the platform even without a guardrail (optional). A 60 cm guardrail is mandatory only for the 4th and 5th steps.

- Two devices block any accidental opening: anti opening/closing rigid bars and hinges in galvanized steel
- Thermo-shrinkable plastic package with showcard
- Ergonomic reinforced non-skid rubber feet
- Non-skid aluminium steps 8 cm
- Distance between steps 20 cm
- Thickness when closed 22 cm
- Top platform 20x70 cm

- On demand (see numbers in the pictures):
- 1) Combination guardrail + 2 handrails of cm 60 (SPPLUS08/C)
Guardrail without handrails (SPPLUS08)
 - 2) Kit 2 wheels



Reinforcements on all step available (additional price)