


# Specifications

| MODELS                         | IWP™-20S   |        | IWP™-25S   |        | IWP™-30S   |        |
|--------------------------------|------------|--------|------------|--------|------------|--------|
|                                | US         | Metric | US         | Metric | US         | Metric |
| Working height*                | 26 ft 6 in | 8.24 m | 30 ft 5 in | 9.44 m | 35 ft 6 in | 11 m   |
| Platform height                | 20 ft 6 in | 6.24 m | 24 ft 5 in | 7.44 m | 29 ft 6 in | 9 m    |
| <b>A</b> Horizontal outreach** | 2 ft 2 in  | .66 m  | —          | —      | —          | —      |
| <b>B</b> Height - stowed:      |            |        |            |        |            |        |
| fully lowered                  | 6 ft 4 in  | 1.93 m | 6 ft 4 in  | 1.93 m | 6 ft 4 in  | 1.93 m |
| base raised                    | 6 ft 6 in  | 1.98 m | 6 ft 6 in  | 1.98 m | 6 ft 6 in  | 1.98 m |
| <b>C</b> Length                | 5 ft       | 1.52 m | 5 ft       | 1.52 m | 5 ft       | 1.52 m |
| <b>D</b> Width - standard base | 2 ft 8 in  | .81 m  | 2 ft 8 in  | .81 m  | —          | —      |
| wide base                      | 3 ft 4 in  | 1.02 m | 3 ft 4 in  | 1.02 m | 3 ft 4 in  | 1.02 m |
| Corner access***               | 6 in       | .15 m  | 6 in       | .15 m  | 7 in       | .18 m  |



| PRODUCTIVITY                   |                 |              |                 |              |                 |              |
|--------------------------------|-----------------|--------------|-----------------|--------------|-----------------|--------------|
| Lift capacity: ANSI/CE         | 350 lbs         | 159 kg       | 350 lbs         | 159 kg       | 350 lbs         | 159 kg       |
| CSA                            | 300 lbs         | 136 kg       | 300 lbs         | 136 kg       | —               | —            |
| With outreach option           | 300 lbs         | 136 kg       | —               | —            | —               | —            |
| Platform Dimensions (l/w/h)    |                 |              |                 |              |                 |              |
| Standard                       | 27/26/44.75 in  | 69/66/114 cm | 27/26/44.75 in  | 69/66/114 cm | 27/26/44.75 in  | 69/66/114 cm |
| Gated standard                 | 27/26/44.75 in  | 69/66/114 cm | 27/26/44.75 in  | 69/66/114 cm | 27/26/44.75 in  | 69/66/114 cm |
| Gated ultra narrow**           | 22/18/44.75 in  | 56/46/114 cm | 22/18/44.75 in  | 56/46/114 cm | 22/18/44.75 in  | 56/46/114 cm |
| Gated narrow                   | 26/20/44.75 in  | 66/51/114 cm | 26/20/44.75 in  | 66/51/114 cm | 26/20/44.75 in  | 66/51/114 cm |
| Front entry gated narrow       | 20/26/44.75 in  | 51/66/114 cm | 20/26/44.75 in  | 51/66/114 cm | 20/26/44.75 in  | 51/66/114 cm |
| Front/side entry extra-large** | 30/28/44.75 in  | 76/71/114 cm | 30/28/44.75 in  | 76/71/114 cm | 30/28/44.75 in  | 76/71/114 cm |
| Standard fiberglass**          | 29/26.5/43.5 in | 74/67/110 cm | 29/26.5/43.5 in | 74/67/110 cm | 29/26.5/43.5 in | 74/67/110 cm |
| Narrow fiberglass**            | 26/22/43.5 in   | 66/56/110 cm | 26/22/43.5 in   | 66/56/110 cm | 26/22/43.5 in   | 66/56/110 cm |

| POWER     |   |
|-----------|---|
| AC models | 110 V / 50-60 Hz or 220 V / 50-60 Hz              |
| DC models | 12V / 110 V / 60 Hz or 110/230 Hz worldwide model |

| WEIGHT****                                |           |        |           |        |           |        |
|---|-----------|--------|-----------|--------|-----------|--------|
| <b>Standard base</b>                      |           |        |           |        |           |        |
| ANSI (AC)                                 | 1,245 lbs | 565 kg | 1,290 lbs | 585 kg | —         | —      |
| ANSI (DC)                                 | 1,345 lbs | 610 kg | 1,390 lbs | 630 kg | —         | —      |
| CE (AC)                                   | 1,245 lbs | 565 kg | 1,290 lbs | 585 kg | —         | —      |
| CE (DC)                                   | 1,345 lbs | 610 kg | 1,390 lbs | 630 kg | —         | —      |
| CSA (AC)                                  | 1,633 lbs | 741 kg | —         | —      | —         | —      |
| CSA (DC)                                  | 1,733 lbs | 786 kg | —         | —      | —         | —      |
| <b>Standard base with outreach option</b> |           |        |           |        |           |        |
| ANSI (AC)                                 | 1,350 lbs | 612 kg | —         | —      | —         | —      |
| ANSI (DC)                                 | 1,450 lbs | 658 kg | —         | —      | —         | —      |
| CE (AC)                                   | 1,350 lbs | 612 kg | —         | —      | —         | —      |
| CE (DC)                                   | 1,450 lbs | 658 kg | —         | —      | —         | —      |
| <b>Wide base</b>                          |           |        |           |        |           |        |
| ANSI (AC)                                 | 1,345 lbs | 610 kg | 1,390 lbs | 630 kg | 1,430 lbs | 649 kg |
| ANSI (DC)                                 | 1,445 lbs | 655 kg | 1,490 lbs | 676 kg | 1,530 lbs | 694 kg |
| CE (AC)                                   | 1,345 lbs | 610 kg | 1,390 lbs | 630 kg | 1,430 lbs | 649 kg |
| CE (DC)                                   | 1,445 lbs | 655 kg | 1,490 lbs | 676 kg | 1,530 lbs | 694 kg |
| CSA (AC)                                  | 1,525 lbs | 692 kg | 1,880 lbs | 853 kg | —         | —      |
| CSA (DC)                                  | 1,625 lbs | 737 kg | 1,980 lbs | 898 kg | —         | —      |
| <b>Wide base with outreach option</b>     |           |        |           |        |           |        |
| ANSI (AC)                                 | 1,450 lbs | 658 kg | —         | —      | —         | —      |
| ANSI (DC)                                 | 1,550 lbs | 703 kg | —         | —      | —         | —      |
| CE (AC)                                   | 1,450 lbs | 658 kg | —         | —      | —         | —      |
| CE (DC)                                   | 1,550 lbs | 703 kg | —         | —      | —         | —      |
| CSA (AC)                                  | 1,633 lbs | 741 kg | —         | —      | —         | —      |
| CSA (DC)                                  | 1,733 lbs | 786 kg | —         | —      | —         | —      |

\* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.  
 \*\* Gated ultra narrow and fiberglass platforms are not available with the outreach option.  
 \*\*\* Corner of platform top rail to corner of wall with ability to rotate leveling jack handle.  
 \*\*\*\* Weight will vary depending on options and/or country standards.

**STANDARDS COMPLIANCE** ANSI A92.3, CSA B354.1, CE Compliance, AS 1418.10

## Features

### EASILY CONFIGURED TO MEET YOUR NEEDS

#### PLATFORM OPTIONS

- Sliding mid-rail standard platform
- Gated standard platform
- Gated ultra narrow platform
- Gated narrow platform
- Standard fiberglass platform
- Narrow fiberglass platform

#### POWER OPTIONS

- AC power 110V / 50-60 Hz
- AC power 220V / 50-60 Hz
- DC power 110V / 50-60 Hz
- DC power 110V / 230V / 50-60 Hz worldwide model
- Power assist option

#### BASE OPTIONS

- Standard base (IWP-20S and 25S only)
- Wide base

### STANDARD FEATURES

#### MEASUREMENTS

##### IWP™-20S

- 26 ft 5 in (8.22 m) working height
- 20 ft 5 in (6.22 m) platform height
- 2 ft 8 in (.81 m) standard base width
- 3 ft 4 in (1.02 m) wide base width
- Outreach option adds 2 ft 2 in (.66 m) of horizontal reach
- Up to 350 lb (159 kg) lift capacity

##### IWP™-25S

- 30 ft 5 in (9.44 m) working height
- 24 ft 5 in (7.44 m) platform height
- 2 ft 8 in (.81 m) standard base width
- 3 ft 4 in (1.02 m) wide base width
- Up to 350 lb (159 kg) lift capacity

##### IWP™-30S

- 35 ft 6 in (11 m) working height
- 29 ft 6 in (9 m) platform height
- 3 ft 4 in (1.02 m) wide base width
- Up to 350 lb (159 kg) lift capacity

#### PRODUCTIVITY

- Sliding mid-rail standard platform
- Auxiliary platform lowering
- Most rigid mast in the industry
- Choose from standard or wide base
- Standard base rolls through standard doorways
- Wide base rolls through double doorways
- AC power to platform
- Dual activated up/down switch
- Ground fault interrupt lower receptacle
- Tie down attachment points
- Overhead crane attachment points
- Wide forklift pockets
- Built-in level sensing with interlocks

#### POWER

- AC power 110V / 50-60 Hz
- AC power 220V / 50-60 Hz
- DC power 110V / 230V / 50-60 Hz with worldwide automatic "smart" charging system



### OPTIONS & ACCESSORIES

#### PRODUCTIVITY

- Gated standard platform
- Gated ultra narrow platform
- Gated narrow platform
- Standard fiberglass platform (not available with outreach)
- Narrow fiberglass platform (not available with outreach)
- Outreach option (IWP-20S only)
- Operational working light and descent alarm package
- Tool tray
- Fluorescent tube caddy
- Platform locating laser light

#### POWER

- Power wheel assist with dual battery package\*
- Dual battery package

\* Adds 12.5 in (.32 m) to unit length and 285 lbs (129 kg) to unit weight

### Genie United States

18340 NE 76th Street  
P.O. Box 97030  
Redmond, Washington 98073-9730

Telephone **(425) 881-1800**  
Toll Free in USA/Canada **800-536-1800**  
Fax (425) 883-3475

### Genie Europe

The Maltings  
Wharf Road  
Grantham NG31 6BH  
U.K.

Telephone **+44 (0)1476 584333**  
Fax +44 (0)1476 584334

Email: [infoeurope@genieind.com](mailto:infoeurope@genieind.com)

### Distributed By:

Effective Date: July, 2007. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade-names of Terex Corporation, Genie Industries, Inc. and/or their subsidiaries in the U.S.A. and many other countries and all rights are reserved. Terex® is a Registered Trademark of Terex Corporation in the U.S.A. and many other countries. Genie® is a Registered Trademark of Genie Industries, Inc. in the U.S.A. and many other countries. Genie is a Terex Company. Copyright © 2007 Terex Corporation.