



SCALISSIMA

Aluminium Telescopic ladder for Professional use

Made of quality-ribbed aluminium for professional usage. The Scalissima's large sturdy, but lightweight, profiles and hinges give maximum performance. The large safe base gives strength and stability in all applications, with durable rubber feet for safe, secure positioning to the ground. Rigorously tested by the official board University of Milan, Scalissima 6/7/8 rungs fully conforms to the European Standard EN131.

Standard features:

- Quality Steel blocking hooks covered in tough durable nylon
- Strong Aluminium hinges for quick positioning
- Tough 3 Pin aluminium hook (for the hinge)
- Kept clean as new (supplied in thermo-shrinkable plastic package).



Quick positioning of the hinges allows:

- 1) Opening and closing as a stepladder without the need to modify the hinge position.
- 2) Rigid Non Collapse position when used as a stepladder by minor adjustment to the hinge position.
- 3) Opening/Closing the ladder for a use as an extension ladder by minor adjustment to the hinge position.

Technical features:

Distance between rungs: 28 cm
Rungs dimensions: 27 x 27 mm
Inner profile: 57 x 27 mm
Outer profile: 65 x 30 mm

	m	m	m	cm	Kg	Kg
6+6	0,97	1,46	3,00	63	9,2	150
7+7	1,25	1,71	3,55	63	9,8	150
8+8	1,25	1,96	4,10	63	11,0	150
9+9	1,53	2,23	4,64	63	12,0	150
10+10	1,53	2,51	5,22	63	13,2	140
11+11	1,81	2,82	5,80	63	14,2	130
12+12	1,81	3,10	6,35	63	15,0	120



Scalissima can be used leant to wall or on stairwells

GUARANTEE
5 YEARS

ISO9000UNIEN287/1
ENISO9606/2



6/7/8 rungs



Via delle Groane, 13 - 24060 Bagnatica BG ITALY - Tel. +39035681663
Fax +39035676321 - Web: <http://www.svelt.it> - E-mail: export@svelt.it

Technical features of this catalogue can be modified without prior notice.