

DONKRAFTE & TRANSPORTMATERIEL / JACKS & TRANSPORT MATERIAL

Drejelige/w. Swivel:

DK Transportruller



Type 1500-4D
Nylon



Type 4000 D
Nylon



Type 6000 D / 12000 D / 12000 D/C
Nylon / Stål/Steel / Composit/Composite

DK-Transportruller tilbyder et bredt og fleksibelt program af transportruller i en af høj kvalitet. Transportrullerne er udført i specialstål og forsynet med kuglelejer med høje bæretal i både drejeskammel og hjul, hvilket er Deres garanti for sikker transport og lang levetid. Gummibeklædte bæreflader. Alle DK-Transportruller er på bærefladerne forsynet med et lag 8 mm skridsikkert vaffelgummi, som forhindrer, at lasten rutscher under transport. Lav placering af bærehåndtag giver ekstra sikkerhed. Bærehåndtagene på alle DK-Transport ruller er placeret min. 25 mm under bærefladen, hvilket forebygger risikoen for klemskafer på brugerens hænder.



Type 4000 DP
Nylon

DK Transport Rollers

DK- Transport Rollers offer a wide and flexible transport roller programme of high quality. The transport rollers are manufactured in special steel and provided with ball bearings with a high strength of lifting in both swivelling bolster and in the rollers, which guarantees a safe transport and a long lifetime. Rubber covered supporting surface. All DK-Transport Rollers are supplied with a cover of 8 mm non-slip chequered rubber on the supporting surface, which prevents sliding of the load during the transport. Low placing of the carrying handles guarantees more safety. The carrying handles of all DK-Transport Rollers are placed minimum 25 mm under the bearing surface, which prevents the risk of damaged hands.

Varenr. / Item no.	Model	Type	Belastning / Capacity kg	Ruller / Rollers	Ruller / Rollers pcs	Rulle dim. / Roller dim. mm	Højde / Height mm	Bæreflade / Plate mm	Vægt / Weight kg
860101	Drejelige / w. Swivel	1500-4D	1500	Nylon	4	81 x 68	115	400 x 400	16
860102	Drejelige / w. Swivel	4000 D	4000	Nylon	4	85 x 90	115	200 x 200	15
860103	Drejelige / w. Swivel	4000 D/C	4000	Composit / Composite	4	85 x 90	115	200 x 200	15
860104	Drejelige / w. Swivel	4000 DP	4000	Nylon	4	85 x 90	115	200 x 200	22
860106	Drejelige / w. Swivel	6000 D	6000	Nylon	8	81 x 68	125	400 x 300	53
860107	Drejelige / w. Swivel	12000 D	12000	Stål / Steel	8	81 x 68	125	400 x 300	65
860108	Drejelige / w. Swivel	12000 D/C	12000	Composit / Composite	8	81 x 68	125	400 x 300	65
860109	Faste / Fixed	2000 F	2000	Nylon	2	85 x 90	105	180 x 105	5
860110	Faste / Fixed	4000 F	4000	Nylon	4	85 x 90	105	220 x 170	10
860111	Faste / Fixed	6000 F	6000	Nylon	6	85 x 90	105	260 x 230	14
860113	Faste / Fixed	8000 F	8000	Stål / Steel	4	85 x 90	105	220 x 170	16
860114	Faste / Fixed	8000 F/C	8000	Composit / Composite	4	85 x 90	105	260 x 230	10
860115	Faste / Fixed	12000 F	12000	Stål / Steel	6	85 x 90	105	260 x 230	26
860116	Faste / Fixed	12000 F/C	12000	Composit	6	85 x 90	105	260 x 230	26



Type 2000 F Nylon



Type 4000 F Nylon / 8000 F Stål/Steel



Type 6000 F Nylon / 12000 F Stål/Steel /
12000 FC Composit/Composite



3 forskellige typer hjul

DK-Transportruller produceres med tre forskellige typer hjul. Ved valg af transportruller skal man derfor være opmærksom på, hvor stor en last rullerne skal transportere og på hvilket underlag transporten skal foregå.

Nylonhjul er den billige løsning til lettere transportopgaver på jævne og rene overflader. Stålhjul er løsningen til transport af tunge laster på rå betongulve eller lignende robuste overflader.

Composithjul er den flexible løsning til transport af laster i alle størrelser på overflader af en hver art.

Three different types of rollers

DK-Transport Rollers are produced with three different types of rollers. Choosing your transport rollers be aware of the weight of the load to be transported and of the floor surfaces.

Nylon rollers are the cheapest solution for easy transports on level and clean surface.

Steel rollers are the solution for transporting of heavy loads on raw concrete floors or similar robust surfaces.

Composit rollers are the flexible solution for transporting of loads of all dimensions on all kind of surfaces.

Sammenbygning medfører nye muligheder

Alle DK-Transportruller type F kan sammenkobles med 25 mm stål rør, hvorved man kan opnå en næsten uendelig forøgelse af rullernes kapacitet ligesom sammenkobling sikrer, at rullerne kører parallelt.

Incorporation result in new possibilities

All DK-Transport can be coupled together with 25 mm steel tubes, which makes it possible to attain to a nearly infinite increasing of the capacity of the rollers, just as an incorporation ensures that the rollers are driving paralelly.



Max. 5 ton Nylon

Bestående af / Consisting of:

1 stk. 860102 - 4000 D

2 stk. 860109 - 2000 F



Max. 8 ton Nylon

Bestående af / Consisting of:

1 stk. 860102 - 4000 D

2 stk. 860110 - 4000 F



Max. 10 ton Nylon

Bestående af / Consisting of:

1 stk. 860102 - 4000 D

2 stk. 860111 - 6000 F



Max. 15 ton Nylon

Bestående af / Consisting of:

1 stk. 860106 - 6000 D

2 stk. 860111 - 6000 F



Max. 30 ton Stål/Steel

Bestående af / Consisting of:

1 stk. 860107 - 12000 D

2 stk. 860115 - 12000 F



Max. 30 ton Composit/Composite

Bestående af / Consisting of:

1 stk. 860108 - 12000 D/C

2 stk. 860116 - 12000 F/C