

## MEDIUM DUTY SCISSOR LIFT



- Safe, light, easy to use and highly manoeuvrable
- High quality robust construction
- A range of maximum lift heights from 840mm to 1550mm
- Manual or battery electric operation
- Optional extras from stainless steel lid to bellows skirt
- Quality British design and manufacture

### Technical Features:

#### All Models

- Single or double lifts available
- Heavy duty arm, bearings and hydraulics
- All wheels are fitted with sealed bearings and polyurethane tyres
- One castor fitted with a total stop brake as standard
- All models fitted with an overload valve and slow lowering valve to control lowering speed
- A unique lift up table top allows safe and easy maintenance- can only be lifted when table is in a closed position
- Each table is issued with operating instructions and a test certificate in conformance with EU Standards EN 1570 and BS:5323:1980
- 

#### Battery electric models

- Models include 12v traction battery and charger
- Safety cut-off bar fitted to the underside of the platform stops table from lowering in the case of an obstruction
- Remote push button control up/down operation
- Emergency stop switch
- Safe design plug-in charger
- Strong electrical flex
- Electrical contacts/motors conform to EQ1570/ EN 60529

## Technical Specification:

### SINGLE SCISSOR TABLES

Capacity	C Raised Height	B Closed Height	Operation	E x A Platform W x L	E x D O/A W x L	F Handle Height	Wheel Dia	Approx Weight	Reference
300KG	840	335	Manual Hyd	500 x 840	500 x1050	860	125	83	SC-300-S-M
300KG	840	335	Battery Electric	500 x 840	500 x1130	860	125	130	SC-300-S-E
500KG	900	340	Manual Hyd	610 x 1030	610 x1320	925	125	109	SC-500-S-M
500KG	900	340	Battery Electric	610 x 1030	610 x1330	925	125	158	SC-500-S-E

### DOUBLE SCISSOR TABLES

Capacity	C Raised Height	B Closed Height	Operation	E x A Platform W x L	E x D O/A W x L	F Handle Height	Wheel Dia	Approx Weight	Reference
125KG	1420	430	Manual Hyd	500 x 840	500 x1090	860	125	100	SC-125-D-M
125KG	1420	430	Battery Electric	500 x 840	500 x1130	860	125	147	SC-125-D-E
300KG	1350	295	Manual Hyd	590 x 840	640 x1190	900	150/125	110	SC-300-D-M
450KG	1550	295	Manual Hyd	610 x 1030	665 x1350	910	150/125	143	SC-450-D-M
450KG	1550	295	Battery Electric	610 x 1030	665 x1350	910	150/125	190	SC-450-D-E

All dimensions are in mm unless otherwise shown

### Options

- Second brake wheel
- Stainless steel top cover
- Plastic roller conveyor top (Increases closed / raised height by 60)
- Ball Top
- Bellows safety skirt
- Rubber Mat

